Prepared by: Steven Sexton WOLVERINE FREIGHTLINER EASTSIDE INC 107 SOUTH GROESBECK HIGHWAY MOUNT CLEMENS, MI 48043 Phone:

City of Rochester Hills SPECIFICATION PROPOSAL

	Description
Price Level	
	SD PRL-23D (EFF:01/21/20)
Data Version	
	SPECPRO21 DATA RELEASE VER 042
Interior Convenience	e/Driver Retention Package
	INTERIOR CONVENIENCE PACKAGE
Vehicle Configuration	n
	108SD CONVENTIONAL CHASSIS
	2022 MODEL YEAR SPECIFIED
	SET BACK AXLE - TRUCK
	TRAILER TOWING PROVISION AT END OF FRAME FOR TRUCK
	LH PRIMARY STEERING LOCATION
General Service	
	TRUCK/TRAILER CONFIGURATION
	DOMICILED, USA (EXCLUDING CALIFORNIA AND CARB OPT-IN STATES)
	CONSTRUCTION SERVICE
	GOVERNMENT BUSINESS SEGMENT
	DIRT/SAND/ROCK COMMODITY
	TERRAIN/DUTY: 100% (ALL) OF THE TIME, IN TRANSIT, IS SPENT ON PAVED ROADS
	MAXIMUM 8% EXPECTED GRADE
	SMOOTH CONCRETE OR ASPHALT PAVEMENT - MOST SEVERE IN-TRANSIT (BETWEEN SITES) ROAD SURFACE
	FREIGHTLINER SD VOCATIONAL WARRANTY
	EXPECTED FRONT AXLE(S) LOAD: 18000.0 lbs



	Description	
	EXPECTED REAR DRIVE AXLE(S) LOAD : 46000.0 lbs	
	EXPECTED GROSS VEHICLE WEIGHT CAPACITY : 64000.0 lbs	
	EXPECTED GROSS COMBINATION WEIGHT : 80000.0 lbs	
Truck Service		
	BELLY PLOW BODY WITH HIGH GROUND CLEARANCE	
	EXPECTED TRUCK BODY LENGTH: 0.0 ft	
	TRUCK AND TRAILER SPECIALTIES INC.	
Tractor Service		
	FLATBED TRAILER	
	SINGLE (1) TRAILER	
Engine		
	CUM L9 370 HP @ 2100 RPM; 2100 GOV RPM, 1250 LB-FT @ 1200 RPM	
Electronic Param	eters	
	70 MPH ROAD SPEED LIMIT	
	CRUISE CONTROL SPEED LIMIT SAME AS ROAD SPEED LIMIT	
	PTO MODE ENGINE RPM LIMIT - 1100 RPM	
	PTO RPM WITH CRUISE SET SWITCH - 700 RPM	
	PTO RPM WITH CRUISE RESUME SWITCH - 800 RPM	
	PTO MODE CANCEL VEHICLE SPEED - 5 MPH	
	PTO GOVERNOR RAMP RATE - 250 RPM PER SECOND	
	NO FLEET SPEC FOR PARAMETERIZATION	
	PTO MINIMUM RPM - 700	
	REGEN INHIBIT SPEED THRESHOLD - 5 MPH	
Engine Equipmer	nt	
	2016 ONBOARD DIAGNOSTICS/2010 EPA/CARB/GHG21 CONFIGURATION	
	NO 2008 CARB EMISSION CERTIFICATION	
	STANDARD OIL PAN	
	OIL FILL AND DIPSTICK LOCATED FOR ENHANCED SERVICEABILITY	
	SIDE OF HOOD AIR INTAKE WITH FIREWALL MOUNTED DONALDSON AIR CLEANER	
Application Version		11/19/2020 3:54 PM
Data Version PRL-23D.042 Rochester Hills TA Swap Ldr		Page 2 of 15

DR 12V 160 AMP 28-SI QUADRAMOUNT PAD ALTERNATOR WITH REMOTE BATTERY VOLT SENSE

(3) DTNA GENUINE, FLOODED STARTING, MIN 2850CCA, 525RC, THREADED STUD BATTERIES

BATTERY BOX FRAME MOUNTED

STANDARD BATTERY JUMPERS

LH BATTERY BOX MOUNTED AS FAR AFT AS POSSIBLE, NO GREATER THAN 60 INCHES BACK OF CAB

WIRE GROUND RETURN FOR BATTERY CABLES WITH ADDITIONAL FRAME GROUND RETURN

PROVIDE 60 INCHES OF ADDITIONAL BATTERY CABLE

NON-POLISHED BATTERY BOX COVER WITH 3/16 INCH TETHER ON FORWARD SIDE OF COVER/BOX

CAB AUXILIARY POWER CABLE

POSITIVE LOAD DISCONNECT WITH CAB MOUNTED CONTROL SWITCH MOUNTED OUTBOARD DRIVER SEAT

POSITIVE AND NEGATIVE POSTS FOR JUMPSTART LOCATED ON FRAME NEXT TO STARTER

CUMMINS TURBOCHARGED 18.7 CFM AIR COMPRESSOR WITH INTERNAL SAFETY VALVE

ELECTRONIC ENGINE INTEGRAL SHUTDOWN PROTECTION SYSTEM

NO RETARDER/ENGINE BRAKE

RH OUTBOARD FRAME MOUNTED VERTICAL AFTERTREATMENT SYSTEM ASSEMBLY WITH TOPSTACK

ENGINE AFTERTREATMENT DEVICE, AUTOMATIC OVER THE ROAD REGENERATION AND DASH MOUNTED REGENERATION REQUEST SWITCH

10 FOOT 00 INCH (120 INCH+0/-5.9 INCH) EXHAUST SYSTEM HEIGHT

RH CURVED TOPSTACK

6 GALLON DIESEL EXHAUST FLUID TANK

100 PERCENT DIESEL EXHAUST FLUID FILL

DIESEL EXHAUST FLUID PUMP MOUNTED AFT OF DIESEL EXHAUST FLUID TANK

LH MEDIUM DUTY STANDARD DIESEL EXHAUST FLUID TANK LOCATION

STANDARD DIESEL EXHAUST FLUID TANK CAP



STAINLESS STEEL AFTERTREATMENT DEVICE/MUFFLER/TAILPIPE SHIELD HORTON DRIVEMASTER ADVANTAGE ON/OFF FAN DRIVE

AUTOMATIC FAN CONTROL WITHOUT DASH SWITCH, NON ENGINE MOUNTED

CUMMINS SPIN ON FUEL FILTER

COMBINATION FULL FLOW/BYPASS OIL FILTER

1115 SQUARE INCH ALUMINUM RADIATOR

ANTIFREEZE TO -34F, OAT (NITRITE AND SILICATE FREE) EXTENDED LIFE COOLANT

GATES BLUE STRIPE COOLANT HOSES OR EQUIVALENT

CONSTANT TENSION HOSE CLAMPS FOR COOLANT HOSES

RADIATOR DRAIN VALVE

1310 ADAPTER FLANGE FOR FRONT PTO PROVISION

ELECTRIC GRID AIR INTAKE WARMER

DELCO 12V 38MT HD STARTER WITH INTEGRATED MAGNETIC SWITCH

Transmission

ALLISON 3000 RDS AUTOMATIC TRANSMISSION WITH PTO PROVISION

Transmission Equipment

ALLISON VOCATIONAL PACKAGE 223 -AVAILABLE ON 3000/4000 PRODUCT FAMILIES WITH VOCATIONAL MODELS RDS, HS, MH AND TRV

ALLISON VOCATIONAL RATING FOR ON/OFF HIGHWAY APPLICATIONS AVAILABLE WITH ALL PRODUCT FAMILIES

PRIMARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

SECONDARY MODE GEARS, LOWEST GEAR 1, START GEAR 1, HIGHEST GEAR 6, AVAILABLE FOR 3000/4000 PRODUCT FAMILIES ONLY

PRIMARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

SECONDARY SHIFT SCHEDULE RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE



PRIMARY SHIFT SPEED RECOMMENDED BY DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE SECONDARY SHIFT SPEED RECOMMENDED BY

DTNA AND ALLISON, THIS DEFINED BY ENGINE AND VOCATIONAL USAGE

FUEL SENSE 2.0 DISABLED - PERFORMANCE - TABLE BASED

DRIVER SWITCH INPUT - DEFAULT - NO SWITCHES

DIRECTION CHANGE ENABLED WITH MULTIPLEXED SERVICE BRAKES - ALLISON 5TH GEN TRANSMISSIONS

VEHICLE INTERFACE WIRING CONNECTOR WITHOUT BLUNT CUTS, AT END OF FRAME

ELECTRONIC TRANSMISSION CUSTOMER ACCESS CONNECTOR FIREWALL MOUNTED

MAGNETIC PLUGS, ENGINE DRAIN, TRANSMISSION DRAIN, AXLE(S) FILL AND DRAIN

PUSH BUTTON ELECTRONIC SHIFT CONTROL, DASH MOUNTED

TRANSMISSION PROGNOSTICS - ENABLED 2013

WATER TO OIL TRANSMISSION COOLER, IN RADIATOR END TANK

TRANSMISSION OIL CHECK AND FILL WITH ELECTRONIC OIL LEVEL CHECK

SYNTHETIC TRANSMISSION FLUID (TES-295 COMPLIANT)

Front Axle and Equipment

MFS-18-133A 18,000# FL1 71.0 INCH KPI/3.74 INCH DROP SINGLE FRONT AXLE

MERITOR 16.5X6 Q+ CAST SPIDER CAM FRONT BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS FRONT BRAKE LINING

CONMET CAST IRON FRONT BRAKE DRUMS

FRONT BRAKE DUST SHIELDS

FRONT OIL SEALS

VENTED FRONT HUB CAPS WITH WINDOW, CENTER AND SIDE PLUGS - OIL

STANDARD SPINDLE NUTS FOR ALL AXLES HALDEX AUTOMATIC FRONT SLACK

ADJUSTERS



STANDARD KING PIN BUSHINGS TRW TAS-85 POWER STEERING POWER STEERING PUMP 2 QUART SEE THROUGH POWER STEERING RESERVOIR OIL/AIR POWER STEERING COOLER CURRENT AVAILABLE SYNTHETIC 75W-90 FRONT AXLE LUBE

Front Suspension

18,000# FLAT LEAF FRONT SUSPENSION GRAPHITE BRONZE BUSHINGS WITH SEALS -FRONT SUSPENSION NO FRONT SUSPENSION OPTIONS FRONT SHOCK ABSORBERS

Rear Axle and Equipment

RT-46-160P 46,000# R-SERIES TANDEM REAR AXLE

5.63 REAR AXLE RATIO

IRON REAR AXLE CARRIER WITH STANDARD AXLE HOUSING

MXL 176T MERITOR EXTENDED LUBE MAIN DRIVELINE WITH HALF ROUND YOKES

MXL 17T MERITOR EXTENDED LUBE INTERAXLE DRIVELINE WITH HALF ROUND YOKES

DRIVER CONTROLLED TRACTION DIFFERENTIAL - BOTH TANDEM REAR AXLES

(1) INTERAXLE LOCK VALVE, (1) DRIVER CONTROLLED DIFFERENTIAL LOCK FORWARD-REAR AND REAR-REAR AXLE VALVE

BLINKING LAMP WITH EACH INTERAXLE LOCK SWITCH, INTERAXLE UNLOCK DEFAULT WITH IGNITION OFF

BLINKING LAMP WITH EACH MODE SWITCH, DIFFERENTIAL UNLOCK WITH IGNITION OFF, ACTIVE <5 MPH

MERITOR 16.5X7 Q+ CAST SPIDER CAM REAR BRAKES, DOUBLE ANCHOR, FABRICATED SHOES

NON-ASBESTOS REAR BRAKE LINING

STANDARD BRAKE CHAMBER LOCATION

CONMET CAST IRON REAR BRAKE DRUMS

REAR BRAKE DUST SHIELDS

Application Version 11.3.004 Data Version PRL-23D.042 Rochester Hills TA Swap Ldr



	Description
	REAR OIL SEALS
	WABCO TRISTOP D LONGSTROKE 2-DRIVE AXLE SPRING PARKING CHAMBERS
	HALDEX AUTOMATIC REAR SLACK ADJUSTERS
	CURRENT AVAILABLE SYNTHETIC 75W-90 REAR AXLE LUBE
	STANDARD REAR AXLE BREATHER(S)
Rear Suspension	
	HENDRICKSON PRIMAAX EX 46,000# REAR AIR SUSPENSION
	HENDRICKSON PRIMAAX 10.00" RIDE HEIGHT
	AXLE CLAMPING GROUP
	52 INCH AXLE SPACING
	MANUAL DUMP VALVE FOR AIR SUSPENSION WITHOUT GAUGE
	INDICATOR LIGHT FOR EACH REAR SUSPENSION CONTROL SWITCH
	DUAL AIR REAR SUSPENSION LEVELING VALVES
	TRANSVERSE CONTROL RODS
	REAR SHOCK ABSORBERS - TWO AXLES (TANDEM) (AIR RIDE SUSPENSION)
Brake System	
	WABCO 4S/4M ABS
	REINFORCED NYLON, FABRIC BRAID AND WIRE BRAID CHASSIS AIR LINES
	FIBER BRAID PARKING BRAKE HOSE
	STANDARD BRAKE SYSTEM VALVES
	STANDARD AIR SYSTEM PRESSURE PROTECTION SYSTEM
	STD U.S. FRONT BRAKE VALVE
	RELAY VALVE WITH 5-8 PSI CRACK PRESSURE, NO REAR PROPORTIONING VALVE
	WABCO SYSTEM SAVER HP WITH INTEGRAL AIR GOVERNOR AND HEATER
	AIR DRYER FRAME MOUNTED
	STEEL AIR TANKS MOUNTED FOR MAX GROUND CLEARANCE, (BELLY PLOW - AA3-073)
	PULL CABLES ON ALL AIR RESERVOIR(S)

Trailer Connections



AIR CONNECTIONS TO END OF FRAME WITH GLAD HANDS FOR TRUCK AND DUST COVERS PRIMARY CONNECTOR/RECEPTACLE WIRED FOR COMBINATION STOP/TURN, CENTER PIN POWERED THROUGH IGNITION WITH STOP SIGNAL PREWIRE PACKAGE SAE J560 7-WAY PRIMARY TRAILER CABLE RECEPTACLE MOUNTED END OF FRAME

UPGRADED CHASSIS MULTIPLEXING UNIT

Wheelbase & Frame

5175MM (204 INCH) WHEELBASE 7/16X3-9/16X11-1/8 INCH STEEL FRAME (11.11MMX282.6MM/0.437X11.13 INCH) 120KSI 1/4 INCH (6.35MM) C-CHANNEL INNER FRAME REINFORCEMENT BODY COMPANY INSTALLED ADDITIONAL FRONT FRAME REINFORCEMENT FOR SNOW PLOW 1600MM (63 INCH) REAR FRAME OVERHANG FRAME OVERHANG RANGE: 61 INCH TO 70 INCH 24 INCH INTEGRAL FRONT FRAME EXTENSION CALC'D BACK OF CAB TO REAR SUSP C/L (CA) : 138.19 in CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA): 115.75 in CALC'D FRAME LENGTH - OVERALL: 331.89 CALCULATED FRAME SPACE LH SIDE : 53.18 in CALCULATED FRAME SPACE RH SIDE: 203.74 in CALC'D SPACE AVAILABLE FOR DECKPLATE : 138.45 in SQUARE END OF FRAME REAR TOW HOOKS FRONT CLOSING CROSSMEMBER

LIGHTWEIGHT HEAVY DUTY ALUMINUM ENGINE CROSSMEMBER STANDARD MIDSHIP #1 CROSSMEMBER(S)

STANDARD REARMOST CROSSMEMBER

HEAVY DUTY SUSPENSION CROSSMEMBER

Chassis Equipment



	Description	
	OMIT FRONT BUMPER, CUSTOMER INSTALLED SPECIAL BUMPER, DOES NOT COMPLY WITH FMCSR 393.203	
	FRONT TOW HOOKS - FRAME MOUNTED	
	HUCK-SPIN ROUND COLLAR CHASSIS FASTENERS	
Fuel Tanks		
	50 GALLON/189 LITER RECTANGULAR ALUMINUM FUEL TANK - LH	
	RECTANGULAR FUEL TANK(S)	
	PLAIN ALUMINUM/PAINTED STEEL FUEL/HYDRAULIC TANK(S) WITH PAINTED BANDS	
	FUEL TANK(S) FORWARD - RAISED MOUNTING PLAIN STEP FINISH	
	FUEL TANK CAP(S)	
	DETROIT FUEL/WATER SEPARATOR WITH WATER IN FUEL SENSOR, HAND PRIMER AND 12 VOLT PREHEATER"	
	EQUIFLO INBOARD FUEL SYSTEM	
	HIGH TEMPERATURE REINFORCED NYLON FUEL LINE	
Tires		
	MICHELIN X WORKS Z 315/80R22.5 20 PLY RADIAL FRONT TIRES	
	MICHELIN X MULTI D 11R22.5 16 PLY RADIAL REAR TIRES	
Hubs		
	CONMET PRESET PLUS PREMIUM IRON FRONT HUBS	
	CONMET PRESET PLUS PREMIUM IRON REAR HUBS	
Wheels		
	MAXION WHEELS 10041 22.5X9.00 10-HUB PILOT 5.25 INSET 5-HAND STEEL DISC FRONT WHEELS	
	MAXION WHEELS 90260 22.5X8.25 10-HUB PILOT 2-HAND HD STEEL DISC REAR WHEELS	
Cab Exterior		
	108 INCH BBC FLAT ROOF ALUMINUM CONVENTIONAL CAB	
	AIR CAB MOUNTING	
Application Versi	en 11.3.004	11/19/2020 3:54 PM

Data Version PRL-23D.042 Rochester Hills TA Swap Ldr

FREIGHTLINER

NONREMOVABLE BUGSCREEN MOUNTED **BEHIND GRILLE** SHORT FENDER WITH MUDFLAP BOLT-ON MOLDED FLEXIBLE FENDER **EXTENSIONS** LH AND RH GRAB HANDLES STATIONARY BLACK GRILLE BLACK HOOD MOUNTED AIR INTAKE GRILLE FIBERGLASS HOOD WITH ACCESS HATCHES DUAL 26 INCH RECTANGULAR POLISHED ALUMINUM AIR HORNS ROOF MOUNTED SINGLE ELECTRIC HORN DUAL HORN SHIELDS DOOR LOCKS AND IGNITION SWITCH KEYED THE SAME **KEY QUANTITY OF 4** REAR LICENSE PLATE MOUNT END OF FRAME HALOGEN COMPOSITE HEADLAMPS WITH BLACK BEZELS SMALL LED AERODYNAMIC MARKER LIGHTS WITH OUTER (2) WIRED TO BATTERY DISCONNECT SWITCH DAYTIME RUNNING LIGHTS - LOW BEAM ONLY INTEGRAL LED STOP/TAIL/BACKUP LIGHTS STANDARD FRONT TURN SIGNAL LAMPS DUAL WEST COAST BRIGHT FINISH HEATED MIRRORS WITH LED LIGHTS AND LH AND RH REMOTE DOOR MOUNTED MIRRORS **102 INCH EQUIPMENT WIDTH** LH AND RH 8 INCH BRIGHT FINISH CONVEX MIRRORS MOUNTED UNDER PRIMARY MIRRORS STANDARD SIDE/REAR REFLECTORS FIXED CAB MOUNTED STEPS LH AND RH FOR

CAB ENTRY, BELLY PLOW BODY WITH HIGH GROUND CLEARANCE DOES NOT COMPLY FMCSR 399

63X14 INCH TINTED REAR WINDOW

TINTED DOOR GLASS LH AND RH WITH TINTED OPERATING WING WINDOWS

RH AND LH ELECTRIC POWERED WINDOWS, PASSENGER SWITCHES ON DOOR(S)

Application Version 11.3.004 Data Version PRL-23D.042 Rochester Hills TA Swap Ldr



	Description
	1-PIECE BONDED HEATED WIPER PARK SOLAR GREEN GLASS WINDSHIELD
	8 LITER (2 GAL) WINDSHIELD WASHER RESERVOIR, CAB MOUNTED, WITH FLUID LEVEL INDICATOR
Cab Interior	
	OPAL GRAY VINYL INTERIOR
	MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR
	MOLDED PLASTIC DOOR PANEL WITHOUT VINYL INSERT WITH ALUMINUM KICKPLATE LOWER DOOR
	BLACK MATS WITH SINGLE INSULATION
	DASH MOUNTED ASH TRAY(S) WITHOUT LIGHTER
	FORWARD ROOF MOUNTED CONSOLE WITH UPPER STORAGE COMPARTMENTS AND ADDITIONAL CENTER COMPARTMENT WITHOUT NETTING
	CENTER STORAGE CONSOLE MOUNTED ON BACKWALL
	(2) CUP HOLDERS LH AND RH DASH
	GRAY/CHARCOAL WING DASH
	SMART SWITCH EXPANSION MODULE
	HEATER, DEFROSTER AND AIR CONDITIONER
	STANDARD HVAC DUCTING
	MAIN HVAC CONTROLS WITH RECIRCULATION SWITCH
	STANDARD HEATER PLUMBING
	VALEO HEAVY DUTY A/C REFRIGERANT COMPRESSOR
	BINARY CONTROL, R-134A
	PREMIUM INSULATION
	SOLID-STATE CIRCUIT PROTECTION AND FUSES
	12V NEGATIVE GROUND ELECTRICAL SYSTEM
	DOME DOOR ACTIVATED LH AND RH, DUAL READING LIGHTS, FORWARD CAB ROOF
	LH AND RH ELECTRIC DOOR LOCKS
	(1) 12 VOLT POWER SUPPLY IN DASH



PREMIUM HIGH BACK AIR SUSPENSION DRIVER SEAT WITH 3 CHAMBER AIR LUMBAR, INTEGRATED CUSHION EXTENSION, FORWARD AND REAR CUSHION TILT, ADJUSTABLE SHOCK ABSORBER

BASIC HIGH BACK NON SUSPENSION PASSENGER SEAT

LH AND RH INTEGRAL DOOR PANEL ARMRESTS

GRAY MORDURA CLOTH DRIVER SEAT COVER GRAY MORDURA CLOTH PASSENGER SEAT

COVER

HIGH VISIBILITY ORANGE SEAT BELTS WITH DRIVER INDICATOR LIGHT AND AUDIBLE ALARM

ADJUSTABLE TILT AND TELESCOPING STEERING COLUMN

4-SPOKE 18 INCH (450MM) STEERING WHEEL

DRIVER AND PASSENGER INTERIOR SUN VISORS

Instruments & Controls

WOODGRAIN DRIVER INSTRUMENT PANEL

WOODGRAIN CENTER INSTRUMENT PANEL

BLACK GAUGE BEZELS

LOW AIR PRESSURE INDICATOR LIGHT AND AUDIBLE ALARM

2 INCH PRIMARY AND SECONDARY AIR PRESSURE GAUGES

DASH MOUNTED AIR RESTRICTION INDICATOR WITH GRADUATIONS

ELECTRONIC CRUISE CONTROL WITH SWITCHES ON AUXILIARY GAUGE PANEL (B DASH PANEL)

KEY OPERATED IGNITION SWITCH AND INTEGRAL START POSITION; 4 POSITION OFF/RUN/START/ACCESSORY

ICU3S, 132X48 DISPLAY WITH DIAGNOSTICS, 28 LED WARNING LAMPS AND DATA LINKED

HEAVY DUTY ONBOARD DIAGNOSTICS INTERFACE CONNECTOR LOCATED BELOW LH DASH

2 INCH ELECTRIC FUEL GAUGE

PROGRAMMABLE RPM CONTROL -ELECTRONIC ENGINE

Application Version 11.3.004 Data Version PRL-23D.042 Rochester Hills TA Swap Ldr



ELECTRICAL ENGINE COOLANT TEMPERATURE GAUGE TRANSMISSION OIL TEMPERATURE INDICATOR LIGHT

ENGINE AND TRIP HOUR METERS INTEGRAL WITHIN DRIVER DISPLAY

ELECTRIC ENGINE OIL PRESSURE GAUGE

AM/FM/WB WORLD TUNER RADIO WITH BLUETOOTH AND USB AND AUXILIARY INPUTS, J1939

DASH MOUNTED RADIO

(2) RADIO SPEAKERS IN CAB

AM/FM ANTENNA MOUNTED ON FORWARD LH ROOF

ELECTRONIC MPH SPEEDOMETER WITH SECONDARY KPH SCALE, WITHOUT ODOMETER

STANDARD VEHICLE SPEED SENSOR WITH ADDITIONAL SIGNAL FOR CUSTOMER USE LOCATED BETWEEN DRIVER AND PASSENGER SEATS

ELECTRONIC 3000 RPM TACHOMETER

(2) TMC RP 1226 ACCESSORY CONNECTORS: (1) LOCATED BEHIND DASH B PANEL AND (1) LOCATED PASSENGER SIDE OF DASH

IGNITION SWITCH CONTROLLED ENGINE STOP

(6) IGN CONTROLLED EXTRA SWITCHES WITH IND LIGHTS WIRED TO POWER DIST BOX WITH RELAYS PROVIDING 20 AMPS PER CIRCUIT TO JUNCTION BLOCK AND 1 CIRCUIT AT 30 AMPS

BW TRACTOR PROTECTION VALVE

TRAILER HAND CONTROL BRAKE VALVE

DIGITAL VOLTAGE DISPLAY INTEGRAL WITH DRIVER DISPLAY

SINGLE ELECTRIC WINDSHIELD WIPER MOTOR WITH DELAY

MARKER LIGHT SWITCH INTEGRAL WITH HEADLIGHT SWITCH AND DUAL CONNECTORS AND SWITCH FOR CUSTOMER FURNISHED SNOW PLOW LIGHTS, LOW BEAMS OFF WITH HIGH BEAMS

TWO VALVE PARKING BRAKE SYSTEM WITH WARNING INDICATOR



Description SELF CANCELING TURN SIGNAL SWITCH WITH
DIMMER, WASHER/WIPER AND HAZARD IN
HANDLE INTEGRAL ELECTRONIC TURN SIGNAL
FLASHER WITH HAZARD LAMPS OVERRIDING
STOP LAMPS Design PAINT: ONE SOLID COLOR Color

CAB COLOR A: N0789EA OMAHA ORANGE ELITE SS BLACK, HIGH SOLIDS POLYURETHANE CHASSIS PAINT POWDER WHITE (N0006EA) FRONT WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) POWDER WHITE (N0006EA) REAR WHEELS/RIMS (PKWHT21, TKWHT21, W, TW) STANDARD E COAT/UNDERCOATING

Certification / Compliance

U.S. FMVSS CERTIFICATION, EXCEPT SALES CABS AND GLIDER KITS

Raw Performance Data

CALCULATED EFFECTIVE BACK OF CAB TO REAR SUSPENSION C/L (CA) : 115.75 in CALC'D SPACE AVAILABLE FOR DECKPLATE : 138.45 in

Extended Warranty

CUM 2017 L9: HD1 MD DTY 5 YEARS / 100,000 MILES / 161,000 KM EXTENDED WARRANTY. FEX APPLIES

CUM 2017 L9: AT3 MD DTY 5 YEARS / 100,000 MILES / 161,000 KM AFTERTREATMENT. FEX APPLIES

ALLISON 3000 RDS SERIES TRANSMISSION EXTEND WARRANTY, 5 YEARS/UNLIMITED MILES FEX



Prepared for: Nick Watterson Roch Hills Coop 1000 Rochester Hills Rochester Hills, MI 48309 Phone: 248-841-2537

Prepared by: Steven Sexton WOLVERINE FREIGHTLINER EASTSIDE INC 107 SOUTH GROESBECK HIGHWAY MOUNT CLEMENS, MI 48043 Phone:

(***) All cost increases for major components (Engines, Transmissions, Axles, Front and Rear Tires) and government mandated requirements, tariffs, and raw material surcharges will be passed through and added to factory invoices.

Application Version 11.3.004 Data Version PRL-23D.042 Rochester Hills TA Swap Ldr

