

**Joint Sealant Material and Applicators****ITB-RH-26-002****Closed Thursday, January 22, 2026 @ 3:00 p.m.****Material Specifications:****Fiber Asphalt Sealant 540, or approved Equal**

Type - blend of high-quality polymer modified asphalt sealant and a mon. of 2% by weight of polyester fibers

Denier - 3 to 6

Length -  $\frac{1}{4}$  +/-0.02 inch (6.35+/-0.51cm)

Specific Gravity - 1.32 to 1.40

Melt Temperature - 475°F (246°C) min.

Tensile Strength - 70,000 PSI min.

Crimps - None

Ignition Temperature - 1000°F min.

Manufacturer (Mark if enclosed)

Data Sheet (Mark if enclosed)

Application Sheet (Mark if enclosed)

Application Life of Product Heated (please specify)

Please specify brand and product name bid:

**Poly-Fiber 544, or approved equal**

Type - Polyester fibers blended with high quality modified asphalt cement

Denier - 3 to 5

Length -  $\frac{1}{4}$  inch (.6cm)

Specific Gravity - 1.38

Melt Temperature - 478°F - 490°F (248°C - 254°C)

Tensile Strength - 78,000 - 88,000 PSI

Elongation at Break 35 - 38%

Manufacturer (Mark if enclosed)

Data Sheet (Mark if enclosed)

Application Sheet (Mark if enclosed)

Application Life of Product Heated (please specify)

Please specify brand and product name bid:

**Roadsaver 515, or approved equal**

Cone Penetration - 50-90

Flow, 140°F (60°C) - 0.5 cm max.

Softening Point - (176°F) (80°C) min.

Resilience - 25-60%

Ductility, 77F (25C) (ASTM D113) - 30 cm min.

Bond, 0°F (-18°C),  $\frac{1}{2}$ " (12.7mm) thickness, 100% extension - Pass 5 cycles

Impact, 0F (-18C) - Pass

Compression Recovery - 0.40 min.

Minimum Application Temperature - 380°F (193°C)

Maximum Heating Temperature - 400°F (204°C)

Manufacturer (Mark if enclosed)

Data Sheet (Mark if enclosed)

Application Sheet (Mark if enclosed)

Application Life of Product Heated (please specify)

Please specify brand and product name bid:

**Crafcro, Inc.**  
**6165 W. Detroit Street**  
**Chandler, AZ 85226****PMG Master Holding, LLC**  
**27989 Van Born Road**  
**Romulus, MI 48174**

Compliant	Exception
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
12 hours	
Crafcro Fiber Asphalt Sealant 540	

Compliant	Exception
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
12 hours	
P&T Products, LLC. - Dura-Fill PF4	

Compliant	Exception
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
12 hours	
Crafcro Poly-Fiber 544	

Compliant	Exception
	X
	X
	X
	X
	X
	X
	X
X	
X	
X	
12 hours	
P&T Products, LLC. - Dura-Fill AR	

Compliant	Exception
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
12 hours	
Crafcro RoadSaver 515	

Compliant	Exception
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
X	
12 hours	
P&T Products, LLC. - Dura-Fill 1190NR	

**Joint Sealant Material and Applicators**

ITB-RH-26-002

Closed Thursday, January 22, 2026 @ 3:00 p.m.

CrafcO, Inc.  
6165 W. Detroit Street  
Chandler, AZ 85226

PMG Master Holding, LLC  
27989 Van Born Road  
Romulus, MI 48174

**Cost Proposal - Materials**

Fiber Asphalt Sealant 540 or approved equal /lb.

Min. Order Amount:

Poly-Fiber 544 or approved equal

Min. Order Amount:

Roadsaver 515 or approved equal

Min. Order Amount:

Please state applicable delivery charges:

2026	2027
\$1.19	\$1.19
2,250 lbs.	
\$1.19	\$1.19
2,250 lbs.	
\$1.19	\$1.19
2,250 lbs.	
none	

2026	2027
\$1.13	\$1.18
2,250 lbs.	
\$1.13	\$1.19
2,250 lbs.	
\$1.13	\$1.18
2,250 lbs.	
n/a	

**Equipment Specifications**

Unit Manufactured by, Model #:

Year of manufacture:

Safety features offered:

**Heating Tank:**

Capacity:

Ambient Temperature:

Insulation:

Loading Hatch:

Heating System:

Temperature Control:

Pumping Unit:

**Sealant Hose and Applicator Wand:**

Length of Hose:

Diameter:

Temperature and pressure handling:

Engine Type; Diesel or Gas:

Fuel Capacity:

Air Compressor:

Were photographs and equipment specs included?

Will the equipment be delivered to the City's garage location? Applicable delivery fee?

Are you able to provide training on these pieces of equipment? Applicable training costs?

Are you able to allow a continuous use of up to 2 melter applicators by the City's DPS Garage?

Can a demo of the product be provided at the City's location of choice?

CrafcO Super Shot 125DC
2020
Agitated Shutoff; Splash-Proof Lid; Integrated Controls
125 Gallons
40°
Yes
Yes
Diesel Fired
Automatic Controls
On Demand Pump
20 Feet
3/4"
not provided
Diesel
32 Gallons
Yes / 50 CFM
Specs provided
Yes. None.
Yes. None.
Yes.
Yes.

SealMaster CP260DA
2014
Wand horn button, anti splash loading batch, and low profile trailer
260 Gallon
300-400° F
1.5" High Temp Ceramic
Anti-splash
Diesel Beckett Burner
Automatic Electronic
Electro-Hydraulic Manifold
23 Feet
3/4"
350° F and hydraulic flow control valve
Diesel
30 Gallon
70 CFM Rotary Vane Air
Specs and Photos provided
Yes.
Yes.
Yes.
Yes.

Does your company accept MasterCard for payment?

Applicable fees or discounts?

Desired Method of Payment:

Terms (discounts offered will be taken):

Yes. None.
Credit Card
Net 30 Days

Yes.
ACH
Net 30