

The point of vision shall be from the height of eye, 3.5 feet above the proposed intersecting elevation to a height of object 3.5 feet above the existing or proposed road centerline and shall be continuously visible within the specified limits.

MINIMUM CORNER SIGHT DISTANCE FOR DRIVEWAYS AND STREETS AT MAJOR ROAD INTERSECTIONS		
MAJOR ROAD	PASSENGER VEHICLES MINIMUM SIGHT DISTANCE IN FEET, BOTH DIRECTIONS	
POSTED OR 85% SPEED IN MPH	2 OR 3 LANE THRU ROAD IN FEET	4 OR 5 LANE THRU ROAD IN FEET
25	280	295
30	335	355
35	390	415
40	445	470
45	500	530
50	555	590
55	610	650

The basic prima facia speed shall be used for gravel roads, unless otherwise approved by the Engineer.

NOTES

- 1. Any deviation from given data requires an engineering study approved by the road agency (City, R.C.O.C., or M.D.O.T.) in accordance with the latest edition AASHTO policy on geometric design.
- 2. This design guide also applies to new Permit and Plat construction projects.
- 3. The above data is based on a left turn maneuver into the intersecting roadway as described in AASHTO. Due to the higher potential accident severity, the left turning sight distance was used to determine the corner sight distanced required. Right turn onto major roads shall have the same sight distances.
- 4. Existing site conditions may require an engineering study to determine sight distance.



I: \ENG\DWG\DETAILS\ROADS\SIGHT DISTANCE-Rds & Paths.DWG